

[] with WOLFF Boost
Compliant with ANSI Standard B30.3-2012-TowerCranes.
Electrical equipment and wiring compliant with European Standard EN 60204-1 and relevant modifications based on the US Standard NFPA-70.
Intermediate steps of 2.5 m (8' 2") are possible.


WOLFF 8038 Clear US

CE
EN 14439 (C25)
BGL C.0.10.0560

Load moment: **max. 6677 kNm**
Lifting capacity: **max. 20.0 t (44093 lb)**
Jib radius: **max. 85.0 m (279')**

WOLFF 8038.20 Clear US - Colli List [Slewing part 85 m (279')]

Pos.	Pce.	Description	Colli	Length [m] (ft)	Width [m] (ft)	Height [m] (ft)	Weight [kg] (ft)	Volume [m³] (ft³)
1	1	Tower head section with HT 23 adapter		6.58 (21' 7")	2.50 (8' 2")	2.86 (9' 4")	17720 (39066)	47.05 (1662)
2	1	Driver's cab with suspension		5.82 (19' 1")	2.23 (7' 3")	2.58 (8' 5")	3430 (7562)	33.49 (1183)
3	1	Counterjib 1 incl. counterjib bracing		12.36 (40' 6")	2.31 (7' 6")	1.62 (5' 3")	8400 (18519)	46.25 (1633)
4	1	Counterjib 2 incl. counterjib bracing		9.45 (31' 1")	3.65 (11' 11")	1.69 (5' 6")	7340 (16182)	58.29 (2058)
5	1	Hoist winch frame Hw 20110 FU incl. 2nd brake with Ø 24 mm hoisting rope [210 m = 595 kg (688' = 1312 lb)]		2.54 (8' 4")	2.57 (8' 5")	1.70 (5' 6")	6080 (13404)	11.10 (392)
6	1	Auxiliary crane hinged cantilever		2.49 (8' 2")	2.79 (9' 1")	0.36 (1' 2")	300 (661)	2.51 (89)
7	1	Jib element 1		10.30 (33' 9")	1.38 (4' 6")	2.65 (8' 8")	8070 (17791)	37.62 (1329)
8	1	Jib element 2 with WOLFF sign		10.35 (33' 11")	1.35 (4' 5")	2.55 (8' 4")	6090 (13426)	35.63 (1258)
9	1	Jib element 3		10.36 (33' 11")	1.35 (4' 5")	2.58 (8' 5")	3955 (8719)	36.09 (1275)
10	1	Jib element 4		5.37 (17' 7")	1.35 (4' 5")	2.56 (8' 8")	1935 (4266)	18.56 (655)
11	1	Jib element 5		2.87 (9' 5")	1.35 (4' 5")	2.01 (6' 7")	1030 (2271)	7.79 (275)
12	1	Jib element 6		5.37 (17' 7")	1.35 (4' 5")	2.01 (6' 7")	1745 (3847)	14.58 (515)
13	1	Jib element 7		10.33 (33' 10")	1.35 (4' 5")	2.01 (6' 7")	2970 (6548)	28.04 (990)
14	1	Jib element 8		10.27 (33' 8")	1.35 (4' 5")	2.00 (6' 6")	2230 (4916)	27.73 (979)
15	1	Jib element 9		10.21 (33' 5")	1.35 (4' 5")	1.94 (6' 4")	1390 (3064)	26.74 (944)
16	1	Jib element 10		10.10 (33' 1")	1.35 (4' 5")	1.93 (6' 3")	970 (2138)	26.32 (929)
17	1	Jib element 11		5.17 (16' 12")	1.35 (4' 5")	1.88 (6' 2")	595 (1312)	13.12 (463)
18	1	Rope swivel crossbeam		10.10 (33' 1")	1.39 (4' 6")	1.58 (5' 2")	250 (551)	22.19 (784)
19	1	Trolley LK 20 with maintenance cage		2.00 (6' 6")	2.08 (6' 9")	1.97 (6' 5")	590 (1301)	8.20 (290)
20	1	Hook block U 20		1.33 (4' 4")	0.68 (2' 2")	0.33 (1' 1")	750 (1653)	0.30 (11)
21	4	Counterweight 2.7 t (5952 lb)		2.28 (7' 5")	1.41 (4' 7")	0.36 (1' 2")	2700 (5952)	1.16 (41)
22	6	Counterweight 4.7 t (10362 lb)		3.91 (12' 9")	1.41 (4' 7")	0.37 (1' 2")	4700 (10362)	2.04 (72)



Dimensions colli list

Standard Truck X 12*

Special transport X 1*

* Slewing part 85 m (279') EXW

WOLFFKRAN GmbH
Austraße 72
74076 Heilbronn
Germany
Tel. +49 7131 9815-0
Fax +49 7131 9815-355
info@wolffkran.de

